



Specifications Sylvania LED Downlight  
Start 5in1 65-185 PIR 18W 1800lm  
111D - 827-830-840 CCT| IP20 - Sensor

[View Product](#)

General Information

|                          |                                |
|--------------------------|--------------------------------|
| SKU                      | 255270                         |
| EAN                      | 5410288531526                  |
| Brand                    | Sylvania                       |
| Manufacturer Name        | ST DLIGHT 5IN1 65-185 1800 PIR |
| Any Lamp all-in warranty | 3 Years                        |
| Average Lifetime (h)     | 55000                          |

Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tiltable                    | No                |
| Technology                  | LED Integrated    |
| Replaces (Watt)             | 1x26              |
| Wattage                     | 18                |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Not Dimmable      |
| Colour Code                 | 865 Daylight      |
| Colour temperature (Kelvin) | 6500 Daylight     |
| Colour Rendering (Ra)       | 80-89             |
| Colour of Light             | White             |
| Light colour options        | Single Color      |

|                          |               |
|--------------------------|---------------|
| Beam Angle (degree)      | 111           |
| Luminous Flux (Lumen)    | 1800          |
| Luminous Efficacy (lm/W) | 100           |
| Power factor             | >0.70         |
| Unified Glare Rating     | < 26          |
| Optical Cover            | Opal          |
| Product Type Category    | LED Downlight |

### Fixture Information

|                        |                        |
|------------------------|------------------------|
| Mounting Method        | Recessed               |
| IP-rating              | IP20                   |
| Impact Protection (IK) | IK05 - 0.70 joule      |
| Operating Temperature  | -20 to +40             |
| Housing                | Plastic                |
| Colour of the Fixture  | Other                  |
| Fixture Connection     | PI [Push-in connector] |

### Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 22  |
| Diameter (mm) | 227 |

### Sensor Information

|                |                                       |
|----------------|---------------------------------------|
| Type of sensor | <b>Why Any-lamp?</b><br>Motion Sensor |
|----------------|---------------------------------------|

 Order from the **largest lighting specialist** in Europe

 **Customised** quotation



Up to **7 years warranty**

 **Easy** return process