



Specifications Philips LED Downlight  
Coreline RS140B 8W 650lm 32D - 840  
Cool White | 95mm - IP65 - Dimmable

[View Product](#)

General Information

|                          |                                |
|--------------------------|--------------------------------|
| SKU                      | 231758                         |
| EAN                      | 8718699382797                  |
| Brand                    | Philips                        |
| Manufacturer Name        | RS140B LED6-32-/840 PSR PI6 WH |
| Any Lamp all-in warranty | 5 Years                        |
| Average Lifetime (h)     | 50000                          |

Technical Information

|                             |                 |
|-----------------------------|-----------------|
| Technology                  | LED Integrated  |
| Wattage                     | 8               |
| Voltage (V)                 | 220-240         |
| Dimmable                    | Dimmable        |
| Colour Code                 | 840 Cool White  |
| Colour temperature (Kelvin) | 4000 Cool White |
| Colour Rendering (Ra)       | 80-89           |
| Colour of Light             | White           |
| Light colour options        | Single Color    |
| Luminous Flux (Lumen)       | 650             |
| Luminous Efficacy (lm/W)    | 82              |
| Beam Angle (degree)         | 32              |

|                 |     |
|-----------------|-----|
| Driver Included | Yes |
|-----------------|-----|

|                       |               |
|-----------------------|---------------|
| Product Type Category | LED spotlight |
|-----------------------|---------------|

## Fixture Information

|                |     |
|----------------|-----|
| Including bulb | Yes |
|----------------|-----|

|                 |          |
|-----------------|----------|
| Mounting Method | Recessed |
|-----------------|----------|

|              |    |
|--------------|----|
| Cut out (mm) | 78 |
|--------------|----|

|               |                    |
|---------------|--------------------|
| Optical Cover | PC (Polycarbonate) |
|---------------|--------------------|

|                      |     |
|----------------------|-----|
| Suitable for Outdoor | Yes |
|----------------------|-----|

|           |      |
|-----------|------|
| IP-rating | IP65 |
|-----------|------|

|                        |                   |
|------------------------|-------------------|
| Impact Protection (IK) | IK02 - 0.20 joule |
|------------------------|-------------------|

|                       |            |
|-----------------------|------------|
| Operating Temperature | -10 to +40 |
|-----------------------|------------|

|         |           |
|---------|-----------|
| Housing | Aluminium |
|---------|-----------|

|                       |       |
|-----------------------|-------|
| Colour of the Fixture | White |
|-----------------------|-------|

|                    |                   |
|--------------------|-------------------|
| Emergency Lighting | No Emergency Unit |
|--------------------|-------------------|

|                     |                    |
|---------------------|--------------------|
| Finish of Reflector | PC (Polycarbonate) |
|---------------------|--------------------|

|              |       |
|--------------|-------|
| Power factor | >0.90 |
|--------------|-------|

|          |    |
|----------|----|
| Tiltable | No |
|----------|----|

|                    |                               |
|--------------------|-------------------------------|
| Fixture Connection | PI [Push-in connector 6-pole] |
|--------------------|-------------------------------|

|        |        |
|--------|--------|
| Series | RS140B |
|--------|--------|

## Dimensions

|             |      |
|-------------|------|
| Height (mm) | 59.9 |
|-------------|------|

|               |    |
|---------------|----|
| Diameter (mm) | 95 |
|---------------|----|



Order from the **largest lighting specialist** in Europe



**Customised** quotation

## Sensor Information



Up to **7 years warranty**



**Easy** return process

|                |           |
|----------------|-----------|
| Type of sensor | No Sensor |
|----------------|-----------|

