



Specifications Noxion LED Panel Delta Pro Econox 32W 3900lm - 830 Warm White | 120x30cm - UGR <22 - Dali Dimmable - Philips Xitanium Driver

[View Product](#)

## General Information

|                          |                                                                  |
|--------------------------|------------------------------------------------------------------|
| SKU                      | 238280                                                           |
| EAN                      | 8719157012560                                                    |
| Brand                    | Noxion                                                           |
| Manufacturer Name        | Noxion LED Panel Econox Xitanium DALI 32W 3900 lm 3000K 300x1200 |
| Any Lamp all-in warranty | 6 Years                                                          |
| Average Lifetime (h)     | 50000                                                            |
| Series                   | Delta Pro                                                        |

## Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Technology                  | LED Integrated     |
| Replaces (Watt)             | 2x36               |
| Wattage                     | 32                 |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 830 Warm White     |
| Colour temperature (Kelvin) | 3000 Warm White    |
| Colour Rendering (Ra)       | 80-89              |
| Colour of Light             | White              |
| Light colour options        | Single Color       |
| Luminous Flux (Lumen)       | 3900               |

|                          |                           |
|--------------------------|---------------------------|
| Luminous Efficacy (lm/W) | 125                       |
| IP-rating                | IP20                      |
| Impact Protection (IK)   | IK02 - 0.20 joule         |
| Fixture Connection       | GST18i3 (2x1mm) male 0.5m |
| Driver Included          | Yes                       |
| Power factor             | >0.90                     |
| Product Type Category    | LED Panel                 |

## Fixture Information

|                       |                          |
|-----------------------|--------------------------|
| Mounting Method       | Recessed                 |
| Unified Glare Rating  | < 22 - for general areas |
| Optical Cover         | PS (Polystyrene)         |
| Operating Temperature | -10 to +40               |
| Emergency Lighting    | No Emergency Unit        |
| Colour of the Fixture | White                    |
| Housing               | PS (Polystyrene)         |
| Colour of material    | White                    |

## Dimensions

|                |          |
|----------------|----------|
| LED panel size | 120x30cm |
| Length (mm)    | 1195     |
| Width (mm)     | 295      |
| Height (mm)    | 32       |

## Sensor Information

Order from the **largest lighting specialist** in Europe  **Customised** quotation

Type of sensor



Up to **7 years warranty**

No Sensor



**Easy** return process